



CompassPlus[®]

Keypad

Available in Black or Silver



4.3-inch Touchscreen

Standby Mode

Durable Aluminum Frame

Backlit
Code-Compliant Keypad

Chrome Accents

Disability Button

RFID Compatible

Built-in Speaker



Technical Specifications

Flush

Keypad (other sizes available)

| | |
|------------------------------------|--|
| Physical Dimensions (WxHxD) | 187 x 338 x 76 mm (7.36 x 13.31 x 3.0 inch) |
| Mounting Height | 945 mm (37.2 inch) Floor to Bottom of Mounting Plate |
| Screen | 4.3-inch display, 480 x 272 pixel, Touchscreen |
| Energy Consumption | Standby 6W, Max 8.5W |
| Standby Mode | Yes, After a Selectable Period of Non-Operation |
| Supply | PoE (IEEE 802.3af) |
| Card Reader Frequency | 125kHz and 13,56MHz |
| Card Reader Protocols | ISO14443A, ISO14443B-2B, ISO14443B-3B, ISO15693 |
| Standard Card Types | MiFare Classic, MiFare 1K, MiFare 4K (All other cards have to be prequalified by our test service center before use.) |
| Range of Application | Temperature: 0 to 60 degrees C (32 to 140 degrees F) |

Flush Mount

Available in Stainless or Brass



Wall & Pedestal

Keypad

| | |
|------------------------------------|--|
| Physical Dimensions (WxHxD) | 137 x 365 x 69 mm (5.4 x 14.4 x 2.7 inch) |
| Mounting Height | 858 mm (33.77 inch) Floor to Bottom of Mounting Plate |
| Screen | 4.3-inch display, 480 x 272 pixel, Touchscreen |
| Energy Consumption | Standby 6W, Max 8.5W |
| Standby Mode | Yes, After a Selectable Period of Non-Operation |
| Supply | PoE (IEEE 802.3af) |
| Card Reader Frequency | 125kHz and 13,56MHz |
| Card Reader Protocols | ISO14443A, ISO14443B-2B, ISO14443B-3B, ISO15693 |
| Standard Card Types | MiFare Classic, MiFare 1K, MiFare 4K (All other cards have to be prequalified by our test service center before use.) |
| Range of Application | Temperature: 0 to 60 degrees C (32 to 140 degrees F) |

Pedestal Mount

Available in Black or Silver

