

OTIS

CompassPlus[®]

Touchscreen

Available in Black or Silver



www.otis.com

© Otis Elevator Company. All rights reserved.

Technical Specifications

Flush

Touchscreen (other sizes available)

Physical Dimensions (WxHxD)	348 x 441 x 76 mm (13.64 x 17.36 x 3.0 inch)
Mounting Height	902 mm (35.5 inch) Floor to Bottom of Mounting Plate
Screen	12-inch display, 800 x 600 pixel, Touchscreen
Energy Consumption	Standby 5W, Max 12W
Standby Mode	Yes, After a Selectable Period of Non-Operation
Supply	PoE (IEEE 802.3af)
Card Reader Frequency	125kHz and 13,56MHz
Card Reader Protocols	ISO14443A, ISO14443B-2B, ISO14443B-3B, ISO15693
Standard Card Types	MiFare Classic, MiFare 1K, MiFare 4K (All other cards have to be prequalified by our test service center before use.)
Range of Application	Temperature: 0 to 60 degrees C (32 to 140 degrees F)

Flush Mount

Available in Stainless or Brass



Wall & Pedestal

Touchscreen

Physical Dimensions (WxHxD)	307 x 316 x 62 mm (12.1 x 12.4 x 2.4 inch)
Mounting Height	961 mm (37.83 inch) Floor to Bottom of Mounting Plate
Screen	12-inch display, 800 x 600 pixel, Touchscreen
Energy Consumption	Standby 5W, Max 12W
Standby Mode	Yes, After a Selectable Period of Non-Operation
Supply	PoE (IEEE 802.3af)
Card Reader Frequency	125kHz and 13,56MHz
Card Reader Protocols	ISO14443A, ISO14443B-2B, ISO14443B-3B, ISO15693
Standard Card Types	MiFare Classic, MiFare 1K, MiFare 4K (All other cards have to be prequalified by our test service center before use.)
Range of Application	Temperature: 0 to 60 degrees C (32 to 140 degrees F)

Pedestal Mount

Available in Black or Silver

