



CompassPlus[®]

Touchpad

Available in Black or Silver



Durable Aluminum Frame

Chrome Accents

Standby Mode

8-inch Touchscreen

Disability Button

RFID Compatible

Built-in Speaker



Technical Specifications

Flush	Touchpad (other sizes available)
Physical Dimensions (WxHxD)	187 x 450 x 76 mm (7.36 x 17.71 x 3.0 inch)
Mounting Height	747 mm (29.4 inch) Floor to Bottom of Mounting Plate
Screen	8-inch display, 480 x 800 pixel, Touchscreen
Energy Consumption	Standby 5W, Max 11W
Standby Mode	Yes, After a Selectable Period of Non-Operation
Supply	PoE (IEEE 802.3af)
Card Reader Frequency	125kHz and 13,56MHz
Card Reader Protocols	ISO14443A, ISO14443B-2B, ISO14443B-3B, ISO15693
Standard Card Types	MiFare Classic, MiFare 1K, MiFare 4K (All other cards have to be prequalified by our test service center before use.)
Range of Application	Temperature: 0 to 60 degrees C (32 to 140 degrees F)

Wall & Pedestal	Touchpad
Physical Dimensions (WxHxD)	137 x 365 x 69 mm (5.4 x 14.4 x 2.7 inch)
Mounting Height	858 mm (33.77 inch) Floor to Bottom of Mounting Plate
Screen	8-inch display, 480 x 800 pixel, Touchscreen
Energy Consumption	Standby 5W, Max 11W
Standby Mode	Yes, After a Selectable Period of Non-Operation
Supply	PoE (IEEE 802.3af)
Card Reader Frequency	125kHz and 13,56MHz
Card Reader Protocols	ISO14443A, ISO14443B-2B, ISO14443B-3B, ISO15693
Standard Card Types	MiFare Classic, MiFare 1K, MiFare 4K (All other cards have to be prequalified by our test service center before use.)
Range of Application	Temperature: 0 to 60 degrees C (32 to 140 degrees F)

Flush Mount

Available in Stainless or Brass



Pedestal Mount

Available in Black or Silver

